

Thermic 23 K

Powered by
**KOHLER
DIESEL**



**PRESSURE
350-500 bar**



Standard equipment:

- 0.966.0006 Gun ML 710 with quick coupling M24-M24



- 0.966.0010 S/S Lance 500 bar L70 M24



- 0.966.0041 Nozzle 050 - (mod. 3521)
- 0.966.0040 Nozzle 040 - (mod. 4018)
- 0.966.0038 Nozzle 028 - (mod. 5015)



- 0.966.0013 High pressure hose 10 m



Optional:

Rotox lance

- cod. 0.966.0019 (mod.3521)
- cod. 0.966.0018 (mod.4018)
- cod. 0.966.0016 (mod.5015)

Pipe cleaning hose 25 m.

- cod. 0.966.0023 (mod.3521/4018)
- cod. 0.966.0022 (mod.5015)

Extension hose 20 m.

- cod. 0.966.0027 (mod.3521)
- cod. 0.966.0026 (mod.4018/5015)

Sand-blasting lance 500 bar

- cod. 0.966.0032 (mod.3521)
- cod. 0.966.0031 (mod.4018)
- cod. 0.966.0030 (mod.5015)

Equipped with:

- Comet TW Premium, TW 500 bar Premium pumps with brass pump head and ceramic pistons
- Kohler engine 12KD477/2
- Gearbox (with 1560 rpm pump)
- Electrical starting
- No engine-oil safety device (oil-alert)
- **Hour counter**
- Automatic decelerator to reduce the number of revs in the bypass phase
- Stainless steel gradual pressure restoration valve with EASY-START
- Thermostatic valve
- Water filter, readily serviceable cartridge type
- Water suction from external tank option (self priming pumps)
- Ø 300 industrial wheels
- Hose reel with 20 mt hose can be mounted on request (cod. 0.966.0035)

	Thermic 23 3521 K	Thermic 23 4018 K	Thermic 23 5015 K
code	0.066.0016	0.066.0015	0.066.0014
operat. pressure	350 bar-5076 psi	400 bar-5801 psi	500 bar-7252 psi
delivery rate	1260 l/h-5.55 GPM	1080 l/h-4.75 GPM	900 l/h-3.96 GPM
engine type/hp	Kohler 12KD477/2 Diesel/23	Kohler 12KD477/2 Diesel/23	Kohler 12KD477/2 Diesel/23
pump type/RPM	TW 500/1560 RPM	TW 500/1560 RPM	TW 500/1560 RPM
max. water inlet temp.	60 °C	60 °C	60 °C
dimension/weight	118,5x74x102cm/235 Kg-518 lbs	118,5x74x102cm/235 Kg-518 lbs	118,5x74x102cm/235 Kg-518 lbs