

### Comfort M



#### Standard equipment:



- 2 x 5.511.1097  
PP brush Ø 483 mm - 19"



- 4.508.0217  
Front squeegee blade L.1270 mm  
Shore 40 Th. 4 mm
- 4.508.0216  
Rear squeegee blade L.1345 mm  
Shore 33 Th. 6 mm

- Suitable for maintenance and deep cleaning of medium and large areas (up to 6.000 m<sup>2</sup>)
- More than 90/120 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic control system for brush rotation and detergent water outflow
- Antifoam device
- Self-levelling brush plate
- Hour meter
- High-performance batteries resulting in high-working efficiency.



Watch the video on youtube:  
[www.youtube.com/lavorpro](http://www.youtube.com/lavorpro)

#### Comfort M 102

|                              |                               |
|------------------------------|-------------------------------|
| code                         | 8.578.0004                    |
| power supply                 | 36V                           |
| scrubbing/squeegee width     | 1020/1250 mm                  |
| max working capacity         | 7140 m <sup>2</sup> /h        |
| solution tank capacity       | 200 l/52.84 gal               |
| recovery tank capacity       | 210-240 l/55.5-63.4 gal       |
| traction type/power          | front motorwheel/900 W        |
| RPM/pressure on the brushes  | 150/120 kg/246 lbs            |
| brush motor power            | 1500 W                        |
| max gradient empty/full tank | 10%/8%                        |
| depression/vacuum motor      | 1800 mmH <sub>2</sub> O/550 W |
| dimensions/weight            | 190x112x145 cm/342 kg         |



The unique anti foam device dramatically reduces the foam generation and prevents it from touching the suction motor, thus protecting its operation. The electronic floating switch stops suction when the tank is full. Large tank opening for fast and easy cleaning and sanification.

The strong V-shaped floor squeegee made of steel profile is widely adjustable and allows to combine the operation of the rubber blades with the high suction power, to get a perfect drying result on every surface. The special filter box retains solid debris and prevents the obstruction of the suction hose.



**Optional accessories:**



- 0.107.0009 Battery box Pb-acid 36V 360Ah C5
- 0.107.0012 Gel battery box 36V 320Ah C5



- 0.108.0003 Battery Charger 24/36V 50/60A - 220-240/50-60




- 4.508.1167 Polyurethane front blade L.1270 TH. 4
- 4.508.0897 Polyurethane rear blade L.1345 TH. 6



- 2x 5.511.1098 Tynex brush Ø 483 mm-19"
- 2x 5.511.1128 PP 0,3 brush Ø 483 mm-19"



- 2x 5.511.1206 PES brush Ø 483 mm - 19"



- 2x 5.511.1099 EWU pad driver Ø 483 mm-19"



- 6.508.0034 - Ø 483 mm - 19"- beige (5 pcs.)
- 6.508.0041 - Ø 483 mm - 19"- green (5 pcs.)
- 6.508.0048 - Ø 483 mm - 19"- black (5 pcs.)



Comfort M scrubbers are easy to use thanks to the simple and user friendly controls. From the control panel the operator can adjust the maximum forward speed and the quantity of cleaning solution outflow, selecting the options most suitable to the dirt type. Job is simplified and made faster by the automatic lifting of the squeegee and of the brush plate.

Thanks to the optimal weight distribution and to the use of strong oil-proof polyurethane wheels the drive is perfect in all working conditions. The emptying of the solution water tank is quick with a simple and easy accessible mechanical tap.

