

CRL 120

NEW

AVAILABLE IN 2 VERSIONS

+ 3.554.0051
With electric motor
MNF 230V 50 Hz




+ 3.554.0052
With internal
combustion engine
**Loncin LC148F-
2S BA**

OPTIONAL



Standard accessories:



0.968.0005



10 m

0.968.0007

Equipped with:

- Tank in high strength polyethylene
- Very low barycentre that guarantees stability
- Complete emptying even on ground that is not perfectly flat
- Lever spray gun with nozzle and diffuser
- External filter
- Tubular frame with detachable handles
- Frame support foot part of the frame, not removable
- Optional hose reel on request

Both codes needs to be ordered to receive the finished product

	CRL 120 with electric motor	CRL 120 with internal combustion engine
code	0.068.0003 + 3.554.0051	0.068.0003 + 3.554.0052
operat. pressure	20 bar-2900 psi	20 bar-2900 psi
delivery rate	1200 l/h-5.55 GPM	1200 l/h-5.55 GPM
Power	Electric motor 230V ~ 50Hz	Engine Loncin LC148F-2S BA
Solution tank capacity	120 lt.	120 lt.
High pressure hose	10 m.	10 m.

Optional:

- 0.966.0067 ABS Hose reel (hose not included)
- 0.966.0075 Sheet metal hose reel (hose not included)
- 0.966.0072 ABS Hose reel hose included 20 m
- 0.966.0073 ABS Hose reel hose included 40 m
- 3.697.0083 **KILLVIR PLUS:** Multi-surface instant purifying API recommended against Covid-19 | Source WHO – World Health Organization guideline