

HMR



NEW



CL 6.0

STANDARD EQUIPMENT

- 0.966.0083 gun GH 301 with swivel



- 0.966.0084 Lance M22 high/low pressure



- 3.103.0111 nozzle 050 (2015)
- 3.103.0208 nozzle 075 (1521)
- 3.103.0213 nozzle 07 (2021)



- 0.966.0086 High pressure hose 10 m - R2 5/16 (2015)
- 0.966.0112 High pressure hose 10 m - R2 3/8 (1521/2021)



Optional:

Turbo lance


- 6.602.0041 (mod. 2015)
- 6.602.0042 (mod. 1521/2021)

Sand-blasting lance 500 bar

- 6.602.0028 (mod. 2015)
- 6.602.0029 (mod. 1521/2021)

Hose reel

- 0.966.0011 with R2 H.P. Hose (15mt)



Caratteristiche tecniche:

- Integrated elastic joint, for best pump coupling
- 4 poles professional electrical motor (1400 RPM)
- Triplex pump with three ceramic pistons, brass linear pump head
- Low voltage and delayed Total Stop
- Professional pressure unloader valve
- 25 lt fuel tank with level float
- High-pressure detergent suction with proportional detergent regulation
- 2 big solid wheels (260 mm) + 2 pivoting wheels with brake
- "No fuel" indicator
- Temperature setting thermostat
- Safety valve
- Pressure gauge
- Boiler thermal protection
- Contactor and motor protection with amperometric control
- Independent boiler ventilation unit
- Single central bar for vertical lifting with crane or winches
- Steel frame, stainless steel cover
- On request available with stainless steel coil

	HMR 2015	HMR 1521	HMR 2021
code	0.066.0071	0.066.0072	0.066.0073
operat. pressure/max	190/200bar	150/160bar	190/200bar
delivery rate	960 l/h	1260 l/h	1260 l/h
boiler absorbed power	6000W-400V 50Hz	6500W-400V 50Hz	8500W-400V 50Hz
motor/pump type/RPM	CL 6.0/1400	CL 6.0/1400	CL 6.0/1400
max. water inlet/outlet temp.	60/110 °C	60/110 °C	60/110 °C
dimension/weight	90x65x87cm/160 kg	90x65x87cm/160 kg	90x65x87cm/170 kg